

# Bordering on Brilliance.

Border tubing and accent LED lighting allows for creative sign solutions. SloanLED proudly offers three LED tubing solutions to fit your application. We bring more than 20 years of experience in designing and manufacturing high performance, reliable, long-lasting LED border tube products. Successful brands, who mean business, choose SloanLED.

## ColorLINE

ColorLINE LED-based rigid tubing system adds stunning neon-like appeal and increased awareness to any building. Completely assembled and sealed tubes are ready for installation, and offer our brightest tubing light output, and innovative lit, mitered corners.

- Daytime color when non-illuminated\*
- Slim profile similar to standard neon
- High impact acrylic: UV stable, hydrocarbon insensitive, and non-fading
- Product can be cut to custom lengths in the field

# ARRING JIMMY FALL

## SloanLED FlexTAPE

SloanLED FlexTAPE delivers flexibility and fast, easy installation in shallow channel letter and architectural accent applications where space is at a premium.

- Available in White (6500 K, 5000 K, 3500 K) and Red<sup>‡</sup>
- Easy installation with peel-n-stick back
- Can be cut in 50 mm (2") segments for zero waste
- Electrical connectors available for solder-free installation

## **FlexiBRITE**

FlexiBRITE adds neon appeal to any LED-lit sign with the world's first completely flexible LED tubing. FlexiBRITE is field bendable, providing the freedom to create an endless array of profiles, contours, and patterns on the fly. Ideal for exterior and interior lighting applications such as sign perimeters, letters, symbols, accent stripes, borders, and open-face channel letters.

- Daytime color when non-illuminated\*
- Optically modified silicone extrusion: UV stable, hydrocarbon insensitive, and non-fading
- Extremely flexible LED tubing
- Convenient mounting clips and mounting tracks
- Product can be cut to custom lengths in the field

## LEDStripe

For 20 years LEDStripe<sup>®</sup> has added lighting elegance and distinction to buildings worldwide. This patented LED-based rigid tubing system, with its large profile and long runs, has become the border tube system of choice for many retail, restaurant, and lodging chains.

- Daytime color when non-illuminated\*
- High impact acrylic: UV stable, hydrocarbon insensitive, and non-fading
- Can be factory bent to minimum 305 mm (12") radius
- Convenient, weatherproof connectors between sections
- Conforms to UL 48 requirements
- Product can be cut to custom lengths in the field

# Specifications

## ColorLINE

#### Dimensions

Width...... 11 mm (0.44") Base width...... 15 mm (0.59") Height...... 25 mm (1.00") Lengths...... 0.6-m (2-ft); 1.2-m (4-ft); 1.8-m (6-ft); 2.4-m (8-ft)

#### In-field bends

Radial bend...... 5.8 m (19 ft) Flat bend..... 1.8 m (6 ft)

Protection class

#### **Power capacity**

7.3 m (24 ft) per SloanLED 60 W 12 VDC power supply

#### Colors

Red, Orange, Yellow, Green, Blue, White, Warm White

#### Unlit product color chart<sup>+</sup>

Red PANTONE 485 C	Orange PANTONE 151 C	Yellow PANTONE 3975 C
Green PANTONE 355 C	Blue PANTONE 2935 C	



For more information on our Border Tubing & Accent collection of products, visit **SloanLED.com**.

### **FlexiBRITE**

#### Dimensions

#### In-field bends

Radial bend...... 305 mm (12") Flat bend...... 25 mm (1")

Protection class

#### **Power capacity**

6 m (20 ft) per SloanLED 60 W 12 VDC power supply

#### Colors

Ruby Red, Citrus Orange, Noviol Gold, Emerald Green, Bromo Blue, Snow White

#### Unlit product color chart<sup>+</sup>

Ruby Red PANTONE 179 C	Citrus Orange PANTONE 1655 C	Noviol Gold PANTONE 3955 C
Emerald Green PANTONE 2242 C	Bromo Blue PANTONE 2184 C	



#### Power per m/ft

#### Colors

White (6500 K, 5000 K, 3500 K) and  $\mathrm{Red}^{\ddagger}$ 



## **LEDStripe**

#### Dimensions

Width...... 25 mm (1.00") Height...... 43 mm (1.68") Lengths...... 0.3-m (1-ft)\*; 0.6-m (2-ft); 1.2-m (4-ft); 1.8-m (6-ft) 2.4-m (8-ft); 3.0-m (10-ft)

#### In-field bends

Radial bend...... 4.25 m (14 ft) Flat bend..... 5.8 m (19 ft)

Protection class

#### IP66

#### Power capacity

18.3 m (60 ft) per SloanLED 100 W 24 VDC power supply

#### Colors

Red, Orange, Amber, True Yellow, Green, Blue, White (6500 K), Lemon Yellow

#### Unlit product color chart<sup>+</sup>

Red	Orange	Amber	True Yellow
PANTONE 1797 C	PANTONE 1665 C	PANTONE 2012 C	PANTONE 7405 C
Green	Blue	Lemon Yellow	
PANTONE 355 C	PANTONE 2935 C	PANTONE 138 C	

\* U.S. and Canada only

- † "Unlit product color chart" provided as a courtesy to give a general idea of product color. Colors in chart not printed using Plantone inks and may vap from actual Plantone number/color. For an accurate representation of product color, a Plantone Color Guide book should be used, or order a sample part. For more information on Plantone, visit Plantone.com.
- ‡ Red available now. White (6500 K, 5000 K, 3500 K) coming mid-April 2020.

ColorLINE is covered by US and foreign patents pending and covered by the following US patents issued: 6,776,504, 6,969,179, and 7,192,157. FlexiBRITE is covered by US and foreign patents pending and covered by the following US patents issued: 6,776,504 and 7,213,941 and European Patent No. 1756471. LEDStripe is covered by US and foreign patents pending and covered by the following US patents issued: 6,776,504, 6,969,179, and 7,192,157.

#### SloanLED Headquarters 805.676.3200 • info@SloanLED.com

SloanLED Europe b.v. +31 88 12 44 900 • Europe@SloanLED.com



#### SloanLED.com

Specifications subject to change without notice. © 2020 SloanLED Rev E 2020-05-07





Dimensions  $L \times W \times H$ 

Comes in 5-m (6.4-ft) reels

Approx. cut increments

 $5 \text{ m} \times 8 \text{ mm} \times 3 \text{ mm}$ 

 $(16.4' \times 0.3'' \times 0.1'')$ 

50 mm (2")