

We Brighten Your Brands

Product
Guide

Linear Lighting
Solutions



Linear solutions for non-linear challenges.

Linear Lighting from SloanLED is a great solution for illuminating cove, awning, and wall wash applications or to highlight non-illuminated signs.

Sealed to lock out moisture for even the most challenging applications

Easy to conceal at only 0.35" (9 mm) thick

IP66 & 68-rated for indoor/outdoor use

SlimLINER

SlimLINER is the low-profile, outdoor and indoor lighting solution that offers natural white illumination for awnings, vinyl canopies, and accents. The sleek, slender design is ideal for narrow applications traditionally reserved for T4 and T5 fluorescent fixtures.

- Fast, easy installation with versatile mounting options
- Can be cut in the field to custom lengths
- Slim, lightweight, low-profile fixture
- 305 mm (12") bend radius
- Illuminates awnings evenly
- Constant Current Technology (CCT)



Multiple applications. One simple solution.

HighLINER 2 is a unique product that walks the line between sign and indoor/outdoor ambient lighting. Easy installation, high energy savings, and low maintenance, make it perfect for restaurants, c-stores, parking structures, stock rooms, coolers, and car washes.



Wire Nut Housing accessory (P/N 400860) snaps onto ends to cover wire connections and/or bridge distances between lights

Top tier LED offers industry leading performance and efficiency with 100,000 hours L₇₀ life

Co-extruded impact modified acrylic housing diffuses light and protects luminaire to provide long operating life

Easily daisy chain up to six 1.2 m (4 ft) luminaires using lead wires located on both sides of the fixture

HighLINER 2

Designed to replace fluorescent lighting, HighLINER 2 is a versatile product for soffits, awnings, and wall washes, that offers natural, white, outdoor and indoor linear illumination for both new construction and retrofit projects, while saving energy, and reducing maintenance costs, for a brilliant bottom line.

- Easy installation for both new construction and retrofit
- Improves walkway and aisle visibility and building aesthetics
- Fits easily into new or existing interior and exterior spaces
- Illuminates soffits evenly
- Lightweight fixture
- Saves up to 64% energy compared with typical fluorescent fixtures

Specifications

For more information on our Linear Lighting collection of products, visit SloanLED.com.



HighLINER 2

Input power

	System*	Luminaire†
1.2 m (4')	17 W	14.4 W
0.3 m (1')	4 W	3.6 W

System efficacy

5000 K	105 lm/W
3500 K	93 lm/W

Light output (lumens)‡

	5000 K	3500 K
1.2 m (4')	1792	1582
0.3 m (1')	448	395

Protection class

IP66 & IP68§

UL location rating

Dry, damp, and wet locations

Lite rating

100,000 hours (L₇₀)¶

Dimming

Optional Motion Sensing
(see Cold Series Dimming Control data sheet)

* For calculating the maximum number of luminaires that can be connected to the branch circuit, use the SYSTEM INPUT POWER.

† For calculating the maximum number of luminaires that can be connected to a power supply, use the LUMINAIRE INPUT POWER.

‡ Tolerance range for optical and electrical data: ±15%.

§ IP66 & IP68 ratings provide protection for extreme outdoor and wet applications (e.g., car wash) or harsh weather exposure.

¶ Do not mount in a submerged application.

¶ Based on LED component manufacturer data.



SlimLINER

Lumens per fixture

5000 K	970
3500 K	825

In-field bends

Radial bend 305 mm (12")

Estimated product lifetime

50,000 hours (L₇₀)

Protection class

IP66 & IP68§

Efficacy

5000 K	108 lm/W
3500 K	92 lm/W

We Brighten Your Brands

SloanLED Headquarters

805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.

+31 88 12 44 900 • Europe@SloanLED.com



SloanLED.com

Specifications subject to change without notice.

© 2020 SloanLED Rev C 2020-05-07

 **SloanLED**[®]
Leaders in LED Technology